# ProSeries SnowPro Snowblowers



## 60" & 47" SnowPro Highlights

- The electric spout rotator and deflector are standard equipment, NOT an expensive option.
  - High-speed impeller ensures excellent snow throwing. The SwingSteer's<sup>™</sup> 19gpm Auxiliary Hydraulics power the SnowPro through deep snow and drifts.
  - Close coupled with the standard low profile quick attach for excellent visibility and maneuverability in tight working conditions around vehicles, buildings and obstructions.
- The optional pivoting drag bar easily pulls snow back away from doors, buildings and other objects, reducing shoveling and accidental damage.





#### ProSeries SnowPro Snowblowers



## **Specifications**

	47" SnowPro	60" SnowPro
Cutting width	47" (1194 mm)	60" (1524 mm)
Height with discharge chute	61.4" (1560 mm)	61.4" (1560 mm)
Length with quick attach	39.4" (1001 mm)	39.4" (1001 mm)
Weight with quick attach	664 lbs (301 kg)	753 lbs (341.5 kg)
Opening size	48.5" (1231 mm) x 25.4" (645 mm)	61.5" (1562 mm) x 25.4" (645 mm)
Auger diameter	14" (355 mm)	14" (356 mm)
Hydraulic auger drive	Shear bolt protected	Shear bolt protected
Maximum auger speed	188 RPM	188 RPM
Maximum impeller speed	900 RPM	900 RPM
Discharge chute diameter	9.75" (248 mm)	9.75" (248 mm)
Level indicator	Visual (See top left picture above)	Visual (See top left picture above)
Drift knives	Standard	Standard
Electric chute deflector	Standard	Standard
Electric chute rotator	Standard	Standard
Pivoting back-drag bar	Optional	Optional

## **ProSeries** Standard Features

Low profile universal quick attach

"Contractor Grade"

- High strength materials throughout

MAC Company LLC reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information, some items shown may be optional and some products shown may not be available at all dealerships. MAC Company LLC disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information consult your local MAC Company dealer and the operator's manual. Power, (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, MAC Corporation strongly recommends the use of a Rollover Protective Structure, Falling Object Protective Structure and seat belt in all applications. The brochure is intended for the United States and US territories only. For information regarding MAC Company products or services outside these areas see MAC Company's web site. MAC Company does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Products were designed or manufactured. SwingSteer is a registered trademark of MAC Company LLC. The reader is hereby placed on notice of MAC Company, LLC's rights in the United States to patents listed at: www.maccompany.com/patents.

- Robust construction
- Hydraulic hoses, couplers and electrical harnesses are included

### maccompany.com

1740 Main Ave W, Ste F, West Fargo, ND 58078 // 701.203.3811

dealer info