

Proseries 60" BrushPro Cutter



Cutter Mower Highlights

- TruFlex linkage allows 14" lateral and fore-aft travel to follow ground contours.
- Hydraulic drive enables bi-directional cutting blade operation, doubling blade life and reducing sharpening frequency.
- Heavy duty dual belt blade drive delivers positive cutting blade drive.
- Front chain-type and rear rubber shielding are standard for safe operation.
- Heavy-duty reinforced deck top and sides.
- Lift deck for easy clean out and maintenance.
- Optional heavy-duty caster wheels and rear antiscalp roller gives optimum cutting height control.





Proseries 60" BrushPro Cutter







Specifications

Overall width	63.3" (1608 mm)
Cutting width	60" (1524 mm)
Overall length	53.5" (1359 mm)
Overall length w/ optional wheel kit	68.7" (1745 mm)
Weight w/ universal quick attach	961 lbs (436 kg)
Cutting capacity	2" (50.8 mm) diameter
Minimum cut height w / opt. wheel kit	3" (78 mm)
Deck construction	Welded and reinforced 10 ga
Hydraulic deck drive, over pressure protection	High efficiency piston motor
Blade drive from hydraulic motor	Kevlar dual B drive belts
Heavy duty greaseable spindle bearings and seals	Deep groove ball bearings
Bearing protection from dust	Dust slingers built in top and bottom
Dust and debris seal protection	Hardened and replaceable seal surfaces
Severe duty drive with over greasing protection	1.375" (35 mm) pulley drive shaft
Heavy duty cutting blades	.4" (10 mm) x 11" (279 mm)
Lateral and fore - aft float	14" (356 mm)
Full length skid shoes	2" x .25" (51 mm x 6.35 mm)
Front thrown debris protection	Full width chain type - standard
Belt detentioner	Standard
Heavy duty foldable front gauge wheels	Optional
Anti-scalp striping / debris roller	Optional

ProSeriesStandard Features

- Low profile universal quick attach
- Robust construction
- "Contractor Grade"
 - High strength materials throughout
- Hydraulic hoses, couplers and electrical harnesses are included

MAC Company LLC reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information, some items shown may be optional and some products shown may not be available at all dealerships. MAC Company LLC disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information consult your local MAC Company dealer and the operator's manual. Power, (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, MAC Corporation strongly recommends the use of a Rollover Protective Structure, Falling Object Protective Structure and seat belt in all applications. The brochure is intended for the United States and US territories only. For information regarding MAC Company products or services outside these areas see MAC Company's web site. MAC Company does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Products were designed or manufactured. SwingSteer is a registered trademark of MAC Company LLC. The reader is hereby placed on notice of MAC

Company, LLC's rights in the United States to patents listed at: www.maccompany.com/patents.

maccompany.com

1740 Main Ave W, Ste F, West Fargo, ND 58078 // 701.203.3811

dealer info